

ADHESION PRIMER 113

Bonding Materials

Liquid polymer intended to be used as a primer prior to application of cement materials on concrete substrates.



Main Properties and Adjustment:

- Intended to be used as a primer above concrete substrates for materials such as putty, self-leveling materials and cement plaster.
- Significantly improves adhesion to substrate of concrete, prevents cracking.
- Serving as a primer for a self-leveling compound.



Packaging: 5 kg, 18 kg plastic gallons

Consumption: Approx. 200-400 gr/m²

Composition: SBR Latex Polymeric Liquid Adhesive

Substrate: Concrete surfaces, concrete walls, plaster

Technical Data:

- Increases adhesion strength to substrate.

Application:

- Ensure that the substrate is clean from loose parts of concrete, dust, dirt and oils.
- Pour liquid Primer 113 into the bucket; apply with a roller or by brushing. Ensure unified and full absorbance of the substrate up to full covering.
- Apply the compound/adhesive/plaster on the primer in a gluey condition.

Precautions:

- Primer 113 should not be applied in surface temperatures under 5°C or above 35°C.
- The material should be applied according to the "wet on wet" method, without waiting for the drying of the primer. If the primer dried out, this action should be repeated

Cleaning: Tools and hands should be cleaned with running water, for as long as the material is wet.

Storage: In its original package in a shaded and dry location.

Shelf Life: Up to 9 months from the production date.

The Technical Service Department is available to our customers for consultation and guidance. The materials marketed by us are made of the finest components and are under close quality control. However, liability for the adjustment of the material to its use is imposed on the user only. We recommend in any event testing the adjustment of the material to the sought application prior to its use

MISTER FIX[®]
INROM CONSTRUCTION INDUSTRIES