

ACRYLIC MASTIC 530

Sealing Mastic

Acrylic mastic for filling and sealing cracks and anchor drills in internal and external walls.



Main Properties and Adjustment:

- Serving for filling and sealing cracks in walls, shower rooms and around door and window frames
- Excellent adhesion to elements made of concrete, cement plaster, metal, aluminum, wood, gypsum partitions, etc.
- Easy to apply, flexible for a long period, enabling to whitewash and paint.
- Suitable for sealing anchor drills in rigid coverings and external walls.



Packaging: 7 kg. and 25 kg. bucket

Consumption: Approx. 1.5 kg. per liter

Composition: Acrylic materials and admixtures

Substrate: concrete, concrete blocks, wood, metal, aluminum, plaster, etc.

Application:

- Clean the crack on both sides.
- Fill in the cracks with the trowel.
- Level the material and remove surpluses with the trowel.
- Smooth the applied material with a water soaked sponge. Wait several hours for drying prior to any further treatment (painting, etc.)
- Clean with water before the material dries.

Precautions:

530 Acrylic Mastic should not be applied in surface temperatures under 5°C or above 35°C

Cleaning: Tools and hands in water for as long as the material is wet.

Storage: In its original package in a shaded and dry location. **Shelf**

Life: Up to 9 months from the production date

ACRYLIC MASTIC 530

Sealing Mastic



The Technical Service Department is available to our customers for consultation and guidance. The materials marketed by us are made of the finest components and are under close quality control. However, liability for the adjustment of the material to its use is imposed on the user only. We recommend in any event testing the adjustment of the material to the sought application prior to its use

MISTER FIX[®]
INROM CONSTRUCTION INDUSTRIES