

QUICK REPAIRING CEMENT 620

Cement for Repairs

Special cement mixture, suitable for emergency repairs of concrete surfaces.



Main Properties and Adjustment:

- Serving for quick repairs of defects in concrete surfaces and quick closing of gaps.
- Hardens after mixing with water in 20 minutes.

Packaging:	bag of 5 kg., bucket of 20 kg.
Consumption:	Approx. 1.6 kg. per liter.
Composition:	Cement mixture with special accelerating additives.
Substrate:	Wet/moist concrete and plaster.

Application:

- Substrate should be thoroughly cleaned from loose parts, oils, dust, and dirt.
- Wet the surface intended for the repair.
- Pour the contents of the container (20 kg.) into the bucket, add 5-7 liter of water, and thoroughly mix until unified mixture is obtained (a mixture in thickness of plasticine). Add about 1-2 liters of water to 5 kg.
- Water quantities could vary, despite that stated above, due to changes of weather and the like. In any event, the appropriate workability level ought to be achieved.
- Primer preparation – add Cement for Bond of Concrete 340 until obtaining a mixture of cream thickness. Apply the primer mixture with a brush on a moist substrate.
- While the primer is still wet, pour the mixture of for Quick Repairing Cement 620, thoroughly compact the material to the substrate and to the sides.
- Level the repair surface with a trowel.
- Cure and maintain wetness for at least 3 days. It is possible to apply Curing Compounds 360 instead of curing in water.

QUICK REPAIRING CEMENT 620

Cement for Repairs

Precautions:

- Material should not be applied in surface temperatures under 5°C or above 35°C.
- Do not add water to a drying mix.
- It is recommended to work with small quantities of material because the drying time is very quick

Cleaning: Tools and hands should be cleaned with running water, for as long as the material is fresh.

Storage:

In its original package in a shaded and dry location.

Shelf Life:

Up to 9 months from the production date



The Technical Service Department is available to our customers for consultation and guidance. The materials marketed by us are made of the finest components and are under close quality control. However, liability for the adjustment of the material to its use is imposed on the user only. We recommend in any event testing the adjustment of the material to the sought application prior to its use

MISTER FIX[®]
INROM CONSTRUCTION INDUSTRIES